

(12) United States Patent

Liu et al.

(10) Patent No.:

US 9,411,242 B2

(45) Date of Patent:

Aug. 9, 2016

(54) EXPOSURE APPARATUS AND EXPOSURE METHOD THEREOF

(71) Applicant: Semiconductor Manufacturing

International (Shanghai) Corporation,

Shanghai (CN)

Inventors: Chang Liu, Shanghai (CN); Qiang Wu,

Shanghai (CN)

(73) Assignee: SEMICONDUCTOR

MANUFACTURING

INTERNATIONAL (SHANGHAD) **CORPORATION**, Shanghai (CN)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 348 days.

Appl. No.: 14/040,685

Filed: Sep. 29, 2013 (22)

(65)**Prior Publication Data**

> US 2014/0253897 A1 Sep. 11, 2014

(30)Foreign Application Priority Data

Mar. 5, 2013 (CN) 2013 1 0069924

Int. Cl.	
G03B 27/32	(2006.01)
G03B 27/54	(2006.01)
G03B 27/58	(2006.01)
G03F 7/20	(2006.01)
G01D 5/347	(2006.01)
H01L 21/68	(2006.01)
G03F 9/00	(2006.01)
G03F 1/42	(2012.01)
G03F 7/24	(2006.01)
	G03B 27/32 G03B 27/54 G03B 27/58 G03F 7/20 G01D 5/347 H01L 21/68 G03F 9/00 G03F 1/42

(52) U.S. Cl.

CPC G03F 7/70141 (2013.01); G01D 5/34746 (2013.01); G03F 1/42 (2013.01); G03F 7/703 (2013.01); G03F 7/70725 (2013.01); G03F

7/70733 (2013.01); G03F 7/70775 (2013.01); G03F 9/7003 (2013.01); G03F 9/7088 (2013.01); H01L 21/681 (2013.01); H01L 21/682 (2013.01); G03F 7/24 (2013.01)

(58) Field of Classification Search

CPC G01D 5/34746; G03F 1/00; G03F 1/38; G03F 1/42; G03F 7/24; G03F 7/70141; G03F 7/703; G03F 7/70616; G03F 7/70725; G03F 7/70733; G03F 7/70716; G03F 7/70775; G03F 9/70; G03F 9/7003; G03F 9/7007; G03F 9/7011; G03F 9/7088; H01L 21/68; H01L 21/681; H01L 21/682 USPC 310/12.05, 12.06, 12.19; 355/53, 67, 355/71, 72, 75, 77

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

2005/0139790	A1	6/2005	Boogaarts et al.	
2005/0140955	A1*	6/2005	Butler	G03B 27/72
				355/69
2007/0263197	A1*	11/2007	Luttikhuis	G03B 27/53
				355/55

(Continued)

Primary Examiner — Colin Kreutzer (74) Attorney, Agent, or Firm — Anova Law Group, PLLC

(57)ABSTRACT

A wafer alignment system is provided for performing a unidirectional scan-exposure. The wafer alignment system includes a plurality of wafer stages successively moving from a first position to a second position of a base cyclically. The wafer alignment method also includes an encoder plate having a first opening and a second opening. Further, the wafer alignment system includes a plurality of encoder plate readers and a plurality of wafer stage fiducials on the wafer stages. Further, the wafer alignment system also includes an alignment detection unit above the first opening of the encoder plate.

15 Claims, 9 Drawing Sheets

